

Water Conservation Specialists. Established 1979

Utility & Metal Location Equipment

RD316™

Description RD316 Magnetic Locator.

Part No. 10/RD316.

Physical

Construction Water-proof high impact plastic housing.

Aluminum sensor tube.

Ruggedness Withstands 3 ft (1 m) drops onto concrete.

Dimensions 40 inches Long.

Weight 3 lbs with batteries.

Depth Range Up to 15 feet.

Visual Indication Numeric digital bar graph and low battery indicator.

Audio Indication Audio tone through waterproof speaker.

Controls Manual speaker volume and sensitivity, Push button On/Off

Batteries 6 x LR6 (AA) 1.5 V alkaline.

100 hours life, nominal @ 68 °F (20 °C) intermittent use.

Operating

Temperature

Range -20°F to +120°F.

Miscellaneous

Options Comes with carry bag.

Quality Control BS5750/ISO 9001/EN29001.

EMC Complies with FCC requirements.

Complies with European EMC Directive 89/336/EEC.

Warranty 24 months.

Associated Technical Services, Ltd.

524 W. St. Charles Road, Villa Park, IL 60181 www.atslimited.com

24-hour Service Line: (630) 834-1558 • Fax: (630)834-5501 • E-mail: atslimited@aol.com